PROPANE-POWERED MICRO BIRD® G5 FORD - SCHOOL BUS





COUNT ON BLUE BIRD AS THE LEADER OF AFFORDABLE GREEN SOLUTIONS



PROPANE-POWERED MICRO BIRD® G5 FORD - SPECIFICATIONS



BODY DIMENSIONS	MODEL	200	200C
	Maximum passenger capacity	30	24
	Number of rows	5	5
	Exterior length overall	283"	283"
	Exterior width overall	96"	96"
	Exterior height overall	113"	118"
	Interior floor length	177.25"	177.25"
	Interior width at hip	93"	93"
	Interior height at center line	76"	76"
	Entrance door	32" x 80"	32" x 80"
	Side windows	35" x 30"	35" x 30"
	Rear bumper	3/16" x 9.5" with 12" wrap around	
FORD CHASSIS	MODEL	200	200C
	Wheelbase	158"	158"
	Engine	6.8 L gas	
	Transmission	5-speed automatic overdrive	
	GVWR	14,500 lbs (6.8 L)	
	Fuel tank	41 gallons	
	Brakes	4-wheel disc	
	Tires	LT225/75RX16E BSW all-season	
	Alternator	155 amp HD / 225 amp HD	
	Battery	72 amp HR 650 CCA	



- The Propane-Powered Micro Bird® uses Ford's E-450 chassis with 6.8L engine and ROUSH® propane system
- The horsepower and torque provides best in class performance
- Passenger capacity up to 30 passengers
- · Also available with flat floor and wheelchair access door
- A 41 US gallon fuel tank allows the Propane-Powered Micro Bird® to travel up to 320 miles, depending on driving conditions
- Warranted by Ford and ROUSH®
- · Available exclusively at your local Blue Bird Dealer

STANDARD BODY EQUIPMENT	Bumper steel Emergency triangular warning device* Entrance door electric Entrance door grab handle left Floor steel Floor plywood 1/2" (4 ply) Flooring grey rib in aisle Flooring grey smooth under seat Flooring steps grey with white nosing FMVSS seat belt anchorage Heater 20,500 BTU Interior below window embossed aluminum Interior mirror 6" x 16" Joint strength Lift door (Model 200C only) Lights clearance LED Lights dome (4) Lights marker LED Lights stop and tail LED Lights turn LED	Mirrors crossview Mirrors rearview Padding all doors Paint exterior yellow Paint interior white Paint roof white Paint rub rail black Rear door 2 windows Rear door 3 point slide bar latch Rear door retainer* Reflective tape rear emergency exit* Roof bow one piece, hat section type Rub rail floor level Rub rail seat level with wrap around Shut-off valve under body Speakers (2) Stepwell light LED Undercoating Windows back (2) tinted 62% Windows side tinted 62% *Standard in the US, optional in Canada
	Air conditioning Audio / P.A. systems Back-up sensors Barriers	Lift wheelchair tie-down Lights back-up LED Light monitoring system Luggage containment systems

CO₂ emissions* from medium-duty engines

The type of engines used in many commercial and municipal vehicles, such as school buses

25
20
17.5
15
10
Properte Properte Natural Gasoline Gas
Raw Data (metric tons CO: equivalent per unit per year)

Bumper aluminum Driver side auxiliary step Electronic sleeping child monitoring system Emergency equipment Entrance door grab handle right Floor plywood 5/8" (5 ply) marine grade Heater 42,000 BTU Integrated toddler seats Lap and shoulder belt seating

Lift door with tinted windows

Lift wheelchair

Lights back-up LED
Light monitoring system
Luggage containment systems
Reflective exterior signs
Remote / heated mirrors
Rub rail skirt level
Rub rail window level
Seats
Vandal lock system
Video monitoring / tracking system

Video monitoring / tracking system Wheelchair and occupant restraint system Wheelchair lift with interlock device

DISTRIBUTED BY:

More options available: Specifications shown in this brochure were in effect at time of printing. In keeping with its policy of continual improvement, Micro Bird, Inc. reserves the right to change specifications without notice and without incurring obligations.

